
(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION

## (19) World Intellectual Property Organization

International Bureau





## 

(10) International Publication Number WO 2004/036071 A1

(51) International Patent Classification<sup>7</sup>: B23P 11/00

PCT

F16C 11/06,

(74) Agent: FORRESTER KETLEY & CO; Forrester House,

(21) International Application Number:

PCT/GB2003/004397

- (22) International Filing Date: 13 October 2003 (13.10.2003)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0223983.8

15 October 2002 (15.10.2002) GB

- (71) Applicant (for all designated States except US): MINEBEA CO., LTD. [JP/JP]; 4106-73, Oaza Miyota, Miyota-machi, Kitasaku-gun,, Nagano 389-0206 (JP).
- (72) Inventor: and
- (75) Inventor/Applicant (for US only): ESSAM, Steven, Andrew [GB/GB]; c/o NMB-Minebea UK Ltd., Doddington Road, Lincoln LN6 3RA (GB).


- 52 Bounds Green Road, London N11 2EY (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, 1R, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A DEFORMABLE BEARING HOUSING



(57) Abstract: A bearing housing to receive and be deformed around a ball having a predetermined radius R to form a bearing, an inner surface of the bearing housing being generally cup-shaped, having at least approximately circular symmetry around a central axis, and comprising: a cup portion of the radius R shaped to seat closely a first portion of a ball of radius R placed in the bearing housing; and a conforming portion lying in the plane which is perpendicular to the central axis and contains the centre of curvature of the cup portion, there being a clearance between the conforming portion and a second portion of the ball, the clearance being greater than any clearance between the cup portion and the first portion of the ball, the bearing housing being shaped such that, when the bearing housing is deformed around a ball having radius R to form a bearing, the bearing housing is deformed so that the conforming portion matches closely the shape of the second portion of the ball.

